Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	17	(skew$3 NEAR1 ("nand" or "and")) and (skew$3 NEAR1 ("or" or "nor")) and (pull-up or (pull adj1 up)) and (pull-down or (pull adj1 down))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/30 10:38
L2	22	(skew$3 NEAR1 ("nand" or "and")) and (skew$3 NEAR1 ("or" or "nor")) and ("326"/$.ccls. or "327"/$.ccls.)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/30 10:39

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	5	((buffer or driver) and ((logic adj1 gate) or "nand" or "nor") and (data NEAR1 signal$1) and ((control$4 NEAR1 signal$1) or (enable NEAR1 signal$1) or (disable NEAR1 signal$1)) and ((equal WITH transistor$1) or (equiva$4 WITH transistor$1) or ("same" WITH transistor$1))).clm.	US-PGPUB	OR	ON	2005/11/30 10:55